

CAMERA SPECIFICATION

Image Device	1/3" CMOS PC3089	
TV System	PAL	NTSC
Effective Pixels	756*504 pixels	
Pixel pitch	4.80 mm*3.73mm	
Scanning System	2:1 Interlace	
Sync. System	Internal	
Resolution	500TV Lines	
Horizontal Sync Frequency	15.625 kHz	15.734 kHz
Vertical Sync Frequency	50 Hz	60 Hz
Video Output	1.0Vp-p, 75Ohm	
Gamma Consumption	0.45	
AGC	Auto	
S/N Ratio	Better than 46.5dB	
White Balance	Auto	
Electronic Shutter	1/60(NTSC)/1/50(PAL)~1/100,000 Seconds	
BLC	Auto	
Operating Temperature	-20℃ ~ 70℃, RH95%MAX	
Storage Temperature	-40℃ ~ 80℃, RH95%MAX	
Power Supply	<input type="checkbox"/> DC12V	<input type="checkbox"/> DC10V~32V
Waterproof rating	<input type="checkbox"/> IP69K	<input type="checkbox"/> IP67 <input type="checkbox"/> IP66 <input type="checkbox"/> NONWATERPROOF
Viewing Angle	<input type="checkbox"/> 200°	<input type="checkbox"/> 150° <input type="checkbox"/> 120° <input type="checkbox"/> 92° <input type="checkbox"/> 69° <input type="checkbox"/> 45°
Audio	<input type="checkbox"/> Yes	<input type="checkbox"/> No
Minimum Illumination	<input type="checkbox"/> 0 Lux	<input type="checkbox"/> 0.1 Lux
Night vision distance	<input type="checkbox"/> 3~5m	<input type="checkbox"/> 8~10m <input type="checkbox"/> 12~15m <input type="checkbox"/> 20~25m <input type="checkbox"/> 30~35m <input type="checkbox"/> ≥40m
Image mode	<input type="checkbox"/> Mirror	<input type="checkbox"/> Normal <input type="checkbox"/> Mirror/Normal image switch
Heater	<input type="checkbox"/> Yes	<input type="checkbox"/> No
IR-CUT	<input type="checkbox"/> Yes	<input type="checkbox"/> No